



Yale® PE2 & RS2 Ratchet Lever Hoist

- 3/4 to 6 ton capacities
- Link chain models
- Light and portable
- Weatherized load brake
- Requires less handle pull to lift full load

Efficient Yale PE2 & RS2 hoists require relatively little effort to operate. (See handle pull required to lift full load in chart). All controls face the operator for convenience and safety. Free wheeling chain adjustment lever lets you play out the chain quickly and easily on unloaded units for fast hook-ups. Yale PE2 & RS2 ratchet lever hoists have been proven under the toughest of applications.

The PE2 and RS2 are designed for heavy-duty construction and industrial applications. Used to pull, lift, drag or stretch, they feature:

- Tough Aluminum alloy construction and powder coat finish
- Weatherproof for outdoor service
- Simple construction with fewer parts for ease of maintenance and lower inventories
- Hoistaloy hardened steel link type load chain for strength, long wear life and flexibility
- Weatherized Weston-type automatic braking system for positive load control
- Easy, one-hand operation and control
- Forged upper and lower hooks with latches standard
- Free wheeling for fast and easy attachment to load
- Upper and lower Latchlok hooks available for all capacities
- Optional Load Limiter protection device stops transmission of lever forces protecting against dangerous overload
- Optional anchor sling simplifies attachment to allow anchor hook to swivel in tight space applications (3/4 & 1 1/2 ton units only)
- Optional Load Sentry warns of overload condition
- Optional shorter lever for 3/4 & 1 1/2 ton units available
- Optional zinc-plated chain available
- Unlimited lift
- Lifetime warranty
- Metric rated
- Made in U.S.A.

PE2 Link Chain Capacities: 3/4 to 6 Ton

